

PRODUCT: 38 GLASS CLOTH SILICONE TAPE.
Silicone adhesive tape.

FEATURES:

38 is manufactured from 4.8 mils electrical grade fiberglass cloth with high performance silicone adhesive.

For uses in most high temperature industrial applications.

- Thought abrasive resistance.
- Excellence mechanical and electrical properties.
- High conformable, no corrosion, UL approval.
- Flame retardant.
- High tensile strength.
- Meet MIL-I-19166C Type 7 MIL.

TECHNICAL DATA:

ITEM	TEST METHOD	NORMAL	MINIMUM.
Adhesive:		Silicone.	
Carrier:		Fiberglass Cloth.	
Carrier Thickness (mil/mm)	ASTM D 1000	4.80 / 0.120	
Total Thickness (mil/mm)	ASTM D 1000	7.20 / 0.180	6.80 / 0.170
Colour		White.	
Adhesion to steel N/25mm)(g/25mm)(oz/in)	ASTM D 1000	7.80 / 800 / 28	6.3 / 650/ 23
Tensile Strength (N/25mm)(kg/25mm)(lb/in)	ASTM D 1000	588 / 60 / 132	490 / 50/ 110
Elongation (%)	ASTM D 1000	10	8
Dielectric Strength (kV)	ASTM D 1000	3.5	3.0
Class of Insulation (°C)	UL 510	UL H / 200	
Range of Temperature (°C/°F)		-73 ~ 260 / -100 ~500	

SIZE:

Tape Length: (m)	33 meters
Tape Width (mm)	From 3 to 1070 mm

Distribuciones Julmarsa S.L.

Tf: +34 91 7254255
 info@julmarsa.com
 www.julmarsa.com